

HSGQ-810



Product Description

HSGQ-810 is our latest XPON passive optical network communication terminal 8-port MDU, the product supports G/EPON adaptive, provides 8 GE network ports, 1 1.25G SFP slot, metal shell; The stability and wide compatibility of the product are suitable for high-speed interconnection projects such as video surveillance, smart city, and smart transportation, and can work normally under the harsh environment of high and low temperature difference, which can well meet the application of high-speed data transmission.

Technical Parameter

Module	Parameter
User Interface	8×10/100/1000M adaptive RJ45 interface
	1×1.25G SFP slot
PON	1×GPON/EPON Interface Interface type: PX20+
	GPON: upstream 1.25Gbps/downstream 2.5Gbps Transmit optical power: 0~4dBm Optical power: -7 DBM ~-28 DBM
	EPON: upstream 1.25Gbps/downstream 1.25Gbps Transmit optical power: 0~4dBm Optical power: -7 DBM ~-27 DBM
RJ45 Lightning Protection	Common mode 4kV
	Differential mode 2kV
Size	286mm × 192mm × 44mm
Environment	Operating temperature: -30°C~70°C
	Working humidity: 10% ~ 90% (no condensation)
	Storage temperature: -40°C to 80°C
	Storage humidity: 5%~95% (storage temperature)
Power Supply	100~240V AC
Power Consumption	Power: 10W(excluding PoE)

Key Feature

- The point-to-multipoint network topology effectively collects and converges the scattered Ethernet services of users, and provides a standard RJ45 fast Ethernet interface on the user side.
- The dynamic bandwidth allocation mechanism enables all users to share bandwidth more reasonably, achieve reliable quality of service (QoS), and ensure the service quality of different services in the same network
- Support IGMP multicast, efficient use of broadband
- Support multicast VLAN
- Provide remote management via OLT and supports local console management
- Support the loopback detection function of the Ethernet interface on the user side
- Support IEEE 802.1q VLAN protocol
- Support broadcast storm suppression
- Support IEEE802.3x flow control (full duplex)
- Support IEEE 802.1p, CoS protocol
- Support WR and SP queue scheduling algorithms
- Support port speed limiting
- Support wide temperature difference between -30°C and 75°C
- All port support 4KV lightning protection
- Support IPv4 / IPv6

Product Interfaces

Indicator	Description
PWR	Power Status
	Steady on: The device is powered on Off: The device is not powered on
PON	Registration Status
	Steady on: The OLT is successfully registered Flash: Registering to OLT Off: The no signal input or optical signal input is abnormal
	Optical Signals
LOS	Steady red: The no signal input or optical signal input is abnormal Off: The optical input is normal
	LAN Status
Link/1000M	Steady on: The link is properly connected Shiny: Data transfer Off: The link is down
	Fiber Port Status
	Steady on: The link is properly connected Shiny: Data transfer Off: The link is down
ETH	ETH Port Status
	Steady on: The link is properly connected Shiny: Data transfer Off: The link is down

Ordering Information

Product Model	Description
HSGQ-810	8×10/100/1000M RJ45
	1×1.25G SFP slot
	Power supply AC220V

For more information, please visit: <http://www.hsgq.com>

Tel:0755-8175 5526 Fax:0755-8958 2791 Email: hsgq@hsgq.com
 Factory Address:5/F, Bldg C, Zone B, Hongfa Technology Industrial Park, Tangtou Community, Shiyan St., Bao'an District, Shenzhen City, Guangdong Province, PRC China.
 Copyright © 2007-2022 Shenzhen HS Fiber Communication Equipment CO., LTD All Rights Reserved
 Version: V1.0, updated on August 16, 2023.

Attention: Due to product version upgrades or other reasons, the content of this document may be updated from time to time. Unless otherwise agreed.
 All statements, information and recommendations in this document do not constitute any warranty of any kind, express or implied.

